



## Technical Specification - Item 190 (15Q2655838)

### Characteristic

Product name		Liquid-Filled Groundmount Transformer; 3PH, 2500 kVA, HV 11000D , LV 415yn
Country of origin		Turkey
Rated power	[kVA]	2500
Insulation Liquid		Mineral Oil
High voltage	[V]	11000
High voltage tapplings (DETC)		+2 -2 2.5%
Low voltage at no load	[V]	415
High voltage insulation level	[kV]	LI 75 / AC 28 / Um 12
Low voltage insulation level	[kV]	LI - / AC 3 / Um 1.1
Frequency	[Hz]	50
Number of phases		3
Vector group		Dyn11
Ambient temperature	°C	40 / / 20
max./monthly/annual average		
Max. average temperature rise (Oil/Winding)	[C/C]	60 / 65
Surface treatment		Painted, RAL 7033
Altitude (a.s.l.)	[m]	<1000
Location		Indoor/Outdoor

### Performance values

Standards		IEC 60076
Impedance	[%]	6(+/-10%)
No load losses	[W]	3800(+15%)
Load losses at 75 °C	[W]	32000(+15%)

### Preliminary dimensions and weight

Length	[mm]	2101
Width	[mm]	1401
Height	[mm]	1735
Roller distance (c/c)	[mm]	x
Oil Weight	[kg]	883
Total weight	[kg]	4901

### Type of design

Tank construction	Corrugation, Hermetically sealed
Cooling	ONAN
High voltage winding conductor material	Cu
Low voltage winding conductor material	Cu

### Standard Features/Accessories - Item 190

Off-Load Tap Changer  
DIN type HV and LV bushings  
Pressure Relief Valve

## ABB ELEKTRİK SANAYİ A.Ş.